

■■■ MADE IN GERMANY

## DISCOVER NOW THE PFT G4 NEXT GENERATION

Experts, who work hard everyday, do not compromise with their equipment. Just as little as we do when it comes to the quality of our PFT G 4.

More than hundred details were improved so that today, the PFT G 4 presents itself as user-friendly and practice-oriented than ever before!

## Find out about the many benefits by yourself:

- A consolidated tube frame withstands large loads easily.
- Maximum stability due to the robust frame structure with consolidated wheel support.
- Safe transport with a forklift truck thanks to the integrated forklift plates.
- No damage to the fittings and switches since they are protected in the inner contour of the frame.
- Greater transport safety since there are no protruding plugs.
- Large control box: excellent ease of maintenance and optimised dust protection.
- Can also be delivered as a switchable version FC 230/400 V.
- Improved water outlet by tilting the pump and optimum frost protection since the residual water can be drained completely.
- Smooth operation thanks to large fine filters with a small mesh size.
- Easy exchange of the tap fittings.

- Easy-to-fit mixing tube with the help of the new mixing tube support.
- Easy cleaning and maintenance thanks to the optional, interchangeable rubber mixing zone.
- Safe transport thanks to four holders at one height and the reliable folding mechanism.
- Better handling due to two additional grips on the container.
- Large tool box, which is suitable e.g. for supporting the mixing tube cleaner, cleaning shaft and/or spraying gun.
- Air compressor is automatically secured during transport if transportation is done by a crane.
- Protecting the air compressor from dirt with the tool box mounted on it and the optionally available splash flaps.
- The metal cover and optional PVC protective foil protect the fittings from dirt.
- Integrated fixture for the rotor wrench.

- Safe commissioning of the injection hood as the protective grid can remain in the material feeding container.
- Better adjustment of the injection hood thanks to the re-designed support.
- High transport safety thanks to the easily accessible and reinforced lifting brackets.
- Best protection and transport due to the rotating motor protection frame.
- Reduction in the dust exposure: subsequent mounting of the optional deflector prevents air from whirling up in the material feeding container.
- High delivery rate up to 85 l/min in case of a floating screed application (so far only up to 55 l/min) with a simple starr wheel change.
- The feed tray nut can be easily opened even after a long period of operation since the thread is protected from dust.

Perfectly maintenancefriendly thanks to smooth accessibility of the tap fittings and press switches.



Dealer

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG Florpost PFT G 4-GB/03.13/PFT

Knauf PFT GmbH & Co. KG

P. O. Box 60 97343 Iphofen Einersheimer Straße 53 97346 Iphofen Germany Knauf Gips
Dry Construction- and Soil-systems

Knauf AMF Ceiling systems

Knauf Bauprodukte Pro Solutions at Home Knauf Gips / Marmorit
Plaster and facade systems

Knauf Dämmstoffe Polystyrol Insulating Material

Marbos Mortar Systems in Civil Engineering Knauf Insulation Insulating Material: Rock Wool, Glass Wool and Wood Wool

Knauf Integral Gypsum Fibre Technology for Soil, Wall and Ceiling Knauf Perlite AQUAPANEL® Cement Boards, Perlit

Sakret Bausysteme Dry Mortar for New Build and Renovation